

ALUSCREEN FUTURA

- Premium screen fabric with aluminium backing for increased solar reflection
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Certified mould resistance

ANVENDELSER



ANGIVELSER OM VÆVNING

	Semitransparent
	35% polyester, 65% PVC, med aluminium på bagsiden
	320 g/m ²
	0.45 mm
	240 cm
	245 cm

VASKEANVISNINGER



TEKNISKE EGENSKABER

	8
	Flammehæmmende
	Optimeret til arbejdsstationer
	Lav varmetransmittans
	Antimikrobielle (ASTM - SGS)
	Kan anvendes i fugtige områder
	Oeko-Tex
	Særlige farver fra 1'200 m
	Svejsbar

FLAMMEHÆMMENDE

B-s1,d0 (EN 13501-1)
 Class 1 (UNI 8456)
 B1 (DIN 4102-1)
 M1 (NF P 92-503/5/7)
 Type B (BS 5867-2)



Aluscreen Futura

OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
01	4.0	4.0	72.0	24.0	2.0	0.46	0.33
02	4.0	4.0	71.0	25.0	3.0	0.47	0.34
03	5.0	3.0	72.0	25.0	5.0	0.46	0.33
04	4.0	4.0	70.0	26.0	3.0	0.47	0.34
05	4.0	4.0	72.0	24.0	4.0	0.46	0.33

T_V Visible light transmission

R_S Solar reflectance

T_{UV} UV transmission


g_{tot} Total g-value

T_S Solar transmission

A_S Solar absorption

F_C Shading factor

$F_C + g_{tot}$: Værdi beregnet med glas: $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1



De viste farver er ikke bindende