

COLORAMA 1 ALU

- Exclusive Colorama Trevira CS fabric with an aluminium backing for increased heat and light reflection
- Technically superior fabric suitable for curtains and blinds
- Standard 100 by Oeko-Tex® certified, free from harmful substances

ANVENDELSER



ANGIVELSER OM VÆVNING

	Transparent
	Polyester Trevira CS, med aluminium på bagsiden
	140 g/m ²
	0.40 mm
	285 cm
	290 cm
	290 cm

VASKEANVISNINGER



TEKNISKE EGENSKABER

	5-7
	Flammehæmmende
	Optimeret til arbejdsstationer
	Lav varmetransmittans
	Egnet til Wave
	Digital udskrivning
	Oeko-Tex
	Særlige farver fra 520 m

FLAMMEHÆMMENDE

B-s1,d0 (EN 13501-1)
 Class 1 (EN 13773)
 B1 (DIN 4102-1)
 M2 (NF P 92-504)
 NFPA 701
 Type C (BS 5867-2)



Colorama 1 Alu
OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
410	19.4	19.2	40.0	40.8	19.1	0.68	0.49
411	18.0	22.8	33.4	43.8	20.0	0.72	0.52
427	15.2	20.3	33.5	46.2	16.4	0.72	0.52
440	23.6	23.9	36.5	39.6	22.5	0.70	0.51

 T_V Visible light transmission

 R_S Solar reflectance


 T_{UV} UV transmission

 g_{tot} Total g-value


 T_S Solar transmission

 A_S Solar absorption


 F_C Shading factor

 $F_C + g_{tot}$: Værdi beregnet med glas: 0.72 / $U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1



410



411



427



440

De viste farver er ikke bindende