

MULTICOLOUR DIMOUT

- Dimout fabric woven with a multicolour yarn for textured room darkening
- The lighter colour reverse side delivers higher heat reflectance
- Cradle to Cradle Certified™ Bronze
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Washable up to 72°
- Proven acoustic properties

ANVENDELSER



Ikke egnet:
SG 4905

ANGIVELSER OM VÆVNING

	Semimørklægning
	Polyester
	400 g/m ²
	0.80 mm
	315 cm
	320 cm
	320 cm

VASKEANVISNINGER

							
	-1%	-2%	-2.5%	-0.5%			
							
	-1%						
							

TEKNISKE EGENSKABER

	6
	Alpha-w = 0.65 / 0.85
	Flammehæmmende
	Kan anvendes i fugtige områder
	Kun krydsbehandling
	Kun krydsbehandling
	Oeko-Tex, Cradle to Cradle

FLAMMEHÆMMENDE

B-s1,d0 (EN 13501-1)
Class 1 (EN 13773)
Type B (BS 5867-2)



Multicolour Dimout

OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
111	0.2	0.2	48.3	51.5	0.10	0.61	0.44
131	0.1	0.1	48.2	51.7	0.00	0.61	0.44
161	0.0	0.0	47.9	52.1	0.00	0.61	0.44
181	0.0	0.0	48.7	51.3	0.00	0.61	0.44
211	0.2	0.2	48.0	51.8	0.10	0.61	0.44
261	0.0	0.0	48.3	51.7	0.00	0.61	0.44
431	0.0	0.1	48.1	51.8	0.00	0.61	0.44
461	0.0	0.1	48.5	51.4	0.00	0.61	0.44

T_V Visible light transmission

R_S Solar reflectance

T_{UV} UV transmission

g_{tot} Total g-value


T_S Solar transmission

A_S Solar absorption


F_C Shading factor

$F_C + g_{tot}$: Værdi beregnet med glas: $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1


Multicolour Dimout




111




131



161




181



211



261



431



461

De viste farver er ikke bindende