

MULTISCREEN 1%, 5%, 10%

- Screen fabric with superior light control to minimise glare
- Offered in 3 openness factors to suit all building orientations
- Greenguard® certification for low-emission products

ANVENDELSER



ANGIVELSER OM VÆVNING

	1%	5%	10%
	Semitransparent		
	64% PVC, 36% glasfiber		
	440 g/m ²	410 g/m ²	350 g/m ²
	0.55 mm	0.55 mm	0.47 mm
	245 cm	315 cm	315 cm
	250 cm	8.9 cm, 12.7 cm, 250 cm, 320 cm	250 cm, 320 cm

VASKEANVISNINGER



TEKNISKE EGENSKABER

	7-8
	Flammehæmmende
	Optimeret til arbejdsstationer
	Forskellige åbenhedsfaktorer
	Kan anvendes i fugtige områder
	Digital udskrivning
	Greenguard
	Særlige farver fra 10'000 m
	Svejsbar

FLAMMEHÆMMENDE

C-s3,d0 (EN 13501-1)
 Class 1 (BS 476)
 Class 1 (UNI 9176/77)
 B1 (DIN 4102-1)
 M1 (NF P 92-503/5/7)
 Type B (BS 5867-2)
 NFPA 701



Multiscreen 1%, 5%, 10%

OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

Multiscreen 1%							
Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
0702	11.8	14.0	47.0	39.0	0.00	0.64	0.46
0730	5.6	6.0	25.0	69.0	0.01	0.79	0.57
3001	2.8	3.0	9.0	88.0	0.01	0.89	0.64

Multiscreen 5%							
Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
0202	20.6	21.0	69.0	10.0	0.05	0.50	0.36
0207	15.8	17.0	54.0	29.0	0.05	0.60	0.42
0220	19.1	22.0	62.0	16.0	0.06	0.54	0.39
0707	12.7	15.0	37.0	48.0	0.06	0.71	0.50
3001	5.6	6.0	10.0	84.0	0.05	0.89	0.62
3006	5.3	5.0	7.0	88.0	0.06	0.89	0.63
3030	5.4	6.0	5.0	89.0	0.04	0.89	0.64

Multiscreen 10%							
Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
0202	28.7	29.0	63.0	8.0	0.11	0.54	0.39
0207	23.2	25.0	53.0	22.0	0.11	0.61	0.44
0220	26.4	29.0	58.0	13.0	0.10	0.57	0.41
0707	18.3	21.0	34.0	45.0	0.11	0.74	0.53
3001	10.2	10.0	10.0	80.0	0.10	0.89	0.64
3006	9.3	10.0	6.0	84.0	0.12	0.89	0.64
3030	10.8	10.0	5.0	85.0	0.10	0.89	0.64

T_V Visible light transmission

R_S Solar reflectance

T_{UV} UV transmission

g_{tot} Total g-value

T_S Solar transmission

A_S Solar absorption

F_C Shading factor

$F_C + g_{tot}$: Værdi beregnet med glas: $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1

Multiscreen 1%, 5%, 10%


De viste farver er ikke bindende