

PUMA

- Robust blackout fabric with reliable hanging characteristics
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Greenguard® certification for low-emission products

ANVENDELSER



Ikke egnet: SG 4905,
SG 4900, SG 4907

ANGIVELSER OM VÆVNING

● Mørklægning

25% glasfiber, 75% PVC-belagt

407 / 530 g/m²

0.30 / 0.38 mm

← max. → 239 / 295 cm

244 cm, 300 cm

TEKNISKE EGENSKABER

☀ 6

🔥 Flamme hæmmende

💧 Kan anvendes i fugtige områder

🖨 Digital udskrivning

🌿 Oeko-Tex, Greenguard

🎨 Særlige farver fra 1'500 m

📌 Svejsbar

VASKEANVISNINGER



FLAMMEHÆMMENDE

Class 1 (CSE RF)

M1 (NF P 92-503/5/7)

Type B (BS 5867-2)



Puma

OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

Farve	R_s	A_s	F_c	g_{tot}
900	56.0	44.0	0.56	0.40
909	22.0	78.0	0.78	0.56
930	5.0	95.0	0.89	0.64
933	45.0	55.0	0.63	0.45
934	60.0	40.0	0.54	0.39


R_s Solar reflectance

A_s Solar absorption


F_c Shading factor

g_{tot} Total g-value


$F_c + g_{tot}$: Værdi beregnet med glas: $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1



900



909



930



933



934

De viste farver er ikke bindende