

REFLEX

- Aluminium backed Trevira CS fabric with high solar reflectance properties
- Technically superior fabric suitable for curtains and blinds
- Standard 100 by Oeko-Tex® certified, free from harmful substances

ANVENDELSER



ANGIVELSER OM VÆVNING

	blød	stiv
	Semitransparent	
	Polyester Trevira CS, med aluminium på bagsiden	
	190 g/m ²	170 g/m ²
	0.50 mm	0.36 mm
	235 cm	
	240 cm	
		8.9 cm, 12.7 cm, 240 cm

TEKNISKE EGENSKABER

	blød	stiv
	5-6	
	Alpha-w = 0.25	
	Flammehæmmende	
	Optimeret til arbejdsstationer	
	Lav varmetransmittans	
	Egnet til Wave	
		Digital udskrivning
	Oeko-Tex	
	Særlige farver fra 500 m	

VASKEANVISNINGER



Reflex

OPTISKE KOEFFICIENTER OG SOLKOEFFICIENTER ($\pm 5\%$, DIN EN 410)

blød							
Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
111	12.0	11.0	41.0	48.0	12.0	0.68	0.47
116	7.0	9.0	38.0	53.0	7.0	0.69	0.49
119	6.0	8.0	39.0	53.0	6.0	0.69	0.48
911	5.0	7.0	40.0	53.0	5.0	0.67	0.47

stiv							
Farve	T_V	T_S	R_S	A_S	T_{UV}	F_C	g_{tot}
111	11.0	11.0	50.0	39.0	11.0	0.61	0.44
116	6.0	8.0	50.0	42.0	6.0	0.62	0.43
119	7.0	9.0	49.0	42.0	7.0	0.61	0.44
911	3.0	6.0	48.0	46.0	4.0	0.62	0.44

T_V Visible light transmission

R_S Solar reflectance

T_{UV} UV transmission

g_{tot} Total g-value

T_S Solar transmission


A_S Solar absorption

F_C Shading factor


$F_C + g_{tot}$: Værdi beregnet med glas: $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$, DIN EN 13363-1



111



116



119



911

De viste farver er ikke bindende